



Declaration of Conformity – Number 047/10

***Hamberger Flooring GmbH & Co. KG, PO Box 100353,
D-83003 Rosenheim***

hereby declare that the construction product

HARO Parquet 3000 HDF 11mm

produced in the Rosenheim plant,

for use in the building industry, for the interior use as non-load bearing building component in dry areas with the following features/properties*):

Thickness:	<i>11 mm</i>
Reaction to fire:	$\geq D_{FI} - s1^{**})$
Density:	$> 500 \text{ kg/m}^3$
Emission of formaldehyde:	<i>E1</i>
Thermal conductivity:	$0.076 \text{ m}^2\text{K/W}$
Slipperiness:	<i>NPD</i>
Breaking strength:	<i>NPD</i>
Hazard class:	<i>1</i>

corresponds with EN 14342, Annex ZA

Hamberger Flooring GmbH & Co. KG

Peter Hamberger

Stephanskirchen 16 February 2010

*) , **) see back side

****)** **Reaction to fire** (individual verification)

C_{fl}-s1 in the wood species oak and beech, varnished

Evidence of conformity of **reaction to fire with DIN EN 13 501-1** established by:

MPA Stuttgart . Otto-Graf-Institute
Materials Testing Institute . University of Stuttgart
Fire Protection Dept. . Fire Classification of Building Materials
Pfaffenwaldring 4 . D-70569 Stuttgart, Germany

ID No. 0672

Evidence of conformity of **formaldehyde release with DIN EN 717-1** established by:

Fraunhofer-Institute for Wood Research
Wilhelm-Klauditz-Institut (WKI)
Bienroder Weg 54 E . D-38108 Braunschweig, Germany

ID No. 0765

Further applicable standards:

- **DIN EN 12524** Building materials and products; Hygrothermal properties; Tabulated design values