



**Declaration of Conformity – Number 031/08**

***Hamberger Flooring GmbH & Co. KG, PO Box 100353,  
D-83003 Rosenheim***

**hereby declare that the construction product**

**HARO Parquet 2500 HDF 11mm**

**produced in the Rosenheim plant,**

**for use in the building industry, for the interior use as non-load bearing building component in dry areas with the following features/properties\*):**

<b>Thickness:</b>	<i>11 mm</i>
<b>Density:</b>	<i>&gt; 500 kg/m<sup>3</sup></i>
<b>Fire protection:</b>	<i>≥ D<sub>FI</sub> - s1<sup>**</sup>)</i>
<b>Formaldehyde class:</b>	<i>E1</i>
<b>Thermal resistance:</b>	<i>0.076 m<sup>2</sup>K/W</i>

**corresponds with EN 14342, Annex ZA**

**Hamberger Flooring GmbH & Co. KG**

Peter Hamberger

**Stephanskirchen 30 October 2008**

\*) , \*\*) see back side

**\*\*)** **Reaction to fire** (individual verification)

C<sub>fl</sub>-s1 in the wood species oak and beech, varnished

Evidence of conformity of **reaction to fire with DIN EN 13 501-1** established by:

MPA Stuttgart · Otto-Graf-Institute

Materials Testing Institute · University of Stuttgart

Fire Protection Dept. · Fire Classification of Building Materials

Pfaffenwaldring 4 · D-70569 Stuttgart, Germany

ID No. 0672

Evidence of conformity of **formaldehyde release with DIN EN 717-1** established by:

Fraunhofer-Institute for Wood Research

Wilhelm-Klauditz-Institut (WKI)

Bienroder Weg 54 E · D-38108 Braunschweig, Germany

ID No. 0765

Further applicable standards:

- **DIN EN 12524** Building materials and products; Hygrothermal properties; Tabulated design values