



Declaration of Conformity – Number 041/09

***Hamberger Flooring GmbH & Co.KG, PO Box 100353,
D-83003 Rosenheim***

hereby declare that the construction product

HARO Parquet 6000 Strip 12mm

produced in the Rosenheim plant,

**for internal installation other than high moisture content areas
in the building industry, over subfloor installation, with the
following features/properties*):**

Thickness:	<i>12,2 mm</i>
Reaction to fire:	<i>min. D_{FI}- s1^{*)}</i>
Density:	<i>> 500 kg/m³</i>
Emission of formaldehyd:	<i>E1</i>
Thermal conductivity:	<i>0.09 m²K/W</i>
Slipperiness:	<i>NPD</i>
Breaking strength:	<i>NPD</i>
Hazard class:	<i>1</i>

corresponds with EN 14342, Annex ZA

Hamberger Flooring GmbH & Co.KG

Peter Hamberger

Stephanskirchen 01 December 2009

***) see back side:**

Reaction to fire (individual verification)
C_{FI}-s1 in the wood species oak, glued.

Evidence of conformity of **reaction to fire with DIN EN 14 342** chart 1 (CWFT).

Evidence of conformity of **reaction to fire with DIN EN 13 501-1** established by:

MPA Stuttgart · Otto-Graf-Institute
Materials Testing Institute · University of Stuttgart
Fire Protection Dept. · Fire Classification of Building Materials
Pfaffenwaldring 4 · D-70569 Stuttgart, Germany
ID No. 0672

Evidence of conformity of **formaldehyde release with DIN EN 717-1** established by:

Fraunhofer-Institute for Wood Research
Wilhelm-Klauditz-Institut WKI
Bienroder Weg 54 E · D-38108 Braunschweig, Germany
ID No. 0765

Further applicable standards:

- **DIN EN 12524** Building materials and products; Hygrothermal properties; Tabulated design values