

## Technical information

### aqua oil white

Art. no. 408 208



---

Product	For revitalizing high wear and tear, oiled white parquet and retouching small scratches.
Instructions	The floor must be cleaned thoroughly (dust-free) before applying aqua oil white. We recommend you use clean & green active for cleaning. Shake the parquet care product aqua oil white well before use and pour undiluted into a suitable bucket/container. Then apply aqua oil white evenly in thick coats with the flat wet-mop in overlapping straight lines. Always apply lengthways, in the board direction. The floor is accessible again after about 2 hours and can be cleaned after 2 days.
Ingredients	Desiccants free of heavy metals, < 5% non-ionic tensides, wax, vegetable oil components, inorganic pigments and water. Meets the requirements of DIN EN 71 -3 (free of heavy metals).
Technical data	pH value: approx. 8.0 Giscode: O10/GH0 Coverage 1,000 ml cover approx. 50 m <sup>2</sup> 20 - 25 ml/m <sup>2</sup> Shelf life: 3 years Colour: White Form: Liquid

#### Note:



Keep out of reach of children  
Clean work materials with water immediately after use.  
Protect from frost!  
Use opened containers quickly.  
Close containers immediately after use.  
Dispose of dried product residue via residual waste.  
Dispose of liquid product residue via local collection points.

Applying aqua oil white can cause a slight increase in the gloss level.

This technical information is for your guidance and is based on our most up to date knowledge. It makes no representation or warranty, express or implied, as to any specific properties of the described product within the meaning of the statutory warranty regulations.

---

Hamberger Flooring GmbH & Co. KG

P.O. Box 10 03 53

D-83003 Rosenheim, Germany

[www.haro.com](http://www.haro.com)

Phone +49 8031 700-0

Fax +49 8031 700-299

E-mail: [mail@hamberger.de](mailto:mail@hamberger.de)