

Technical information

aqua oil black

Art. no. 408,207



Product	For revitalizing high wear and tear, oiled dark parquet floors and retouching scratches.
Instructions	The floor must be cleaned thoroughly (dust-free) before applying aqua oil black. We recommend you use clean & green active for cleaning. Shake aqua oil black well before use and pour undiluted into a suitable bucket/container. Then apply aqua oil black evenly in thick coats with the flat wet-mop in overlapping straight lines. Always apply lengthways, in the board direction. The floor is accessible again after about 2 hours and can be cleaned after 2 days.
Ingredients	Desiccants free of heavy metals, < 5% non-ionic tensides, wax, vegetable oil components, inorganic pigments and water. Meets the requirements of DIN EN 71 -3 (free of heavy metals).
Technical data	pH value: approx. 8.0 Giscode: O10/GH0 Coverage 1,000 ml cover approx. 50 m ² 20 - 25 ml/m ² Shelf life: 3 years Colour: black Form: Liquid

Note:



Keep out of reach of children
Clean work materials with water immediately after use.
Protect from frost!
Use opened containers quickly.
Close containers immediately after use.
Dispose of dried product residue via residual waste.
Dispose of liquid product residue via local collection points.

Applying aqua oil black can cause a slight increase in the gloss level.

This technical information is for your guidance and is based on our most up to date knowledge. It makes no representation or warranty, express or implied, as to any specific properties of the described product within the meaning of the statutory warranty regulations.